



Audio Video Equipment Standards

**Information Tecnology Services and
Planning, Architectural and Engineering Services
Established Date: July 2016**

Exhibit I Tech Ready Classroom AV Equipment (quantities determined by design) capacity 35 students				as of July 2016
	Item	Features and Performance requirements	Performance Product	
Audio/Video Displays	Laser Video Projector w/ Mount	With HDMI input RS-232 control and HDBaseT Input. Lensing and brightness determined by screen size and room light conditions. Ceiling mount to be compatible with the for selected projector. Must have security features.	Sony VPL-FHZ57W projector or approved equivalent Chief RPA-020 Mount or approved equivalent	
	Projection Screen and Switch Control	Screen size shall be determined by 9' ceiling height mounting needs. Motorized contrast grey preferred. Switch mounted on wall for screen control.	Draper, Da-Lite, or approved equivalent	
	Ceiling Speakers	Must provide appropriate number of speakers for complete room coverage.	Sound Advance, JBL or approved equivalent	
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system		
Control Equipment	Central Room Control TouchPanel Power Connections Power Supply	7" Touch Panel for room control Power over ethernet for touch panel if required Low voltage interface to integrate screen control with control system Power Supply for AMX controller	AMX MSD-701-L or MST-701 AMX PS-POE AF TC AMX PS4.4	
	Master Controller	The NX-2200 / NetLinX® NX Integrated Controller is a programmable network appliance specifically designed to control AV and building technology using multiple analog and digital formats. The NX-2200 provides a scalable platform for the future by combining high performance, backward compatibility and extensive network security features. The NX-2200 is ideal for control and automation of medium-sized rooms and multi-room applications, as it includes more ports and security capabilities than the NX-1200.	AMX NX-2200	
Video Switching / Processing Equipment				
	Scaling AV Switcher	IN-1608 AV switcher. 2 DTP inputs, 4 HDMI inputs, 2 VGA inputs, 3 scaleable outputs with audio level control.	Extron IN1608 MA 70 HDBT HDCP-Compliant Scaling Switcher 60-1238-73	
Video Source equipment	Annotation Tablet w/ 2 Pens and Desk Monitor Arm	Digital HD 18.5" preview monitor with ability to annotate using Smart Technologies software. And Swiveling monitor arm to attach preview monitor to podium	Smart Tablet SP-518NB or approved equivalent Smart Pen 20-01545-20 or approved equivalent Chief monitor arm K1W120B or approved equivalent	
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system		
Complete Podium	Teaching Podium	Native Maple finish, custom base, 23" turret frame with vented rack inserts, trim and finishing kits with custom cut out for specified control panel.	Middle Atlantic L5TURFRW23, L5GTK23NT, FIN-NM, and L5-CUSTPNL-23 Podium with L5-SHOC-XLR-S and L5-Tasklight18 or approved equivalent	
	Networking switch	Policy-based access control, identity and role-aware network, data integrity and confidentiality. Layer 2 threat defense capabilities with integrated security features for flexible collaboration between users on the network. Compliance with Payment Card Industry Data Security Standard (PCI DSS) to meet regulatory mandates. Physical security with cable guard and lock. Ease of Deployment: •Zero touch deployment and ease of troubleshooting •Automatic configuring of the switch based on the type of device connected to the port •State-of-the-art QoS implementation for IP telephony and video Reduce Energy Costs: •Support to monitor, manage and reduce energy consumption of the devices connected to the switch Connectivity: •8-12 Fast Ethernet or Gigabit Ethernet connectivity •Power over Ethernet (PoE) and PoE pass-through •Two 1-Gb Ethernet uplinks	Cisco Catalyst 2960C 8 FE PoE or approved equivalent	
	Power Management Unit	Must have ethernet control	RLNK-SW815R-SP	
	Gooseneck Mic	Also shock mount Mic holder and light. For wireless mic mounted to podium	Clock Audio C34E/SR-RF or approved equivalent	
	Audio Amplifier	Only if Wattage of speakers exceed Extron Crosspoint 40 Amplifier wattage	Extron, QSC, JBL or approved equivalent	
	USB Switcher	Features with emulation for Smart software functionality between PC and laptop. Four-input USB switchers that allow switching between multiple host devices and multiple USB peripherals. Integrator-friendly for implementing USB 2.0 compatible switching. Streamline integration such as: port status indication, RS-232 pass-through, front panel security lockout, and multiple control points. Host and Peripheral Emulation Mode, which provides "keep alive" functionality by continuously mimicking host and keyboard/mouse communications within the switcher. Eliminates the need for enumeration, and reduction in the chance of failed device communications throughout the switching process.	Extron SW4 USB 60-954-02 or approved equivalent	
	Captive Cable Kit	plate with one large hole and two small	Extron 70-317-13 or approved equivalent	
	Grommet Plate	for VGA/Audio Cable	Extron 70-317-12 or approved equivalent	
	Adapters	CSM 6 captive screw to female adapter. Display Port to HDMI adaptor for PC to switcher audio	Extron or approved equivalent	
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system		

Exhibit 2 Classroom Standards		Hi-Tech Ready Classroom AV Equipment (Quantities determined by design) capacity to 99 students		as of July 2016
	Item	Features and Performance requirements	Performance Product	
Audio/Video Displays	Laser Video Projector w/ Mount	With HDMI input RS-232 control and HDBaseT Input. Lensing and brightness determined by screen size and room light conditions. Ceiling mount to be compatible with the for selected projector. Must have security features.	Sony VPL-FHZ57W projector or approved equivalent Chief RPA-020 Mount or approved equivalent	
	Projection Screen and Switch Control	Screen size shall be determined by 9' ceiling height mounting needs. Motorized contrast grey preferred. Switch mounted on wall for screen control.	Draper, Da-Lite, or approved equivalent	
	Ceiling Speakers	Must provide appropriate number of speakers for complete room coverage.	Sound Advance, JBL or approved equivalent	
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system		
Control Equipment	Central Room Control TouchPanel Power Connections Power Supply	7” Touch Panel for room control Power over ethernet for touch panel if required Low voltage interface to integrate screen control with control system Power Supply for AMX controller	AMX MSD-701-L or MST-701 AMX PS-POE AF TC AMX PS4.4	
	Master Controller	The NX-2200 / NetLinx® NX Integrated Controller is a programmable network appliance specifically designed to control AV and building technology using multiple analog and digital formats. The NX-2200 provides a scalable platform for the future by combining high performance, backward compatibility and extensive network security features. The NX-2200 is ideal for control and automation of medium-sized rooms and multi-room applications, as it includes more ports and security capabilities than the NX-1200.	AMX NX-2200	
Video Switching / Processing Equipment	Scaling AV Switcher	IN-1608 AV switcher. 2 DTP inputs, 4 HDMI inputs, 2 VGA inputs, 3 scaleable outputs with audio level control.	Extron IN1608 MA 70 HDBT HDCP-Compliant Scaling Switcher 60-1238-73	
Video Source equipment	Annotation Tablet w/ 2 Pens and Desk Monitor Arm	Digital HD 18.5" preview monitor with ability to annotate using Smart Technologies software. And Swiveling monitor arm to attach preview monitor to podium	Smart Tablet SP-518NB or approved equivalent Smart Pen 20-01545-20 or approved equivalent Chief monitor arm K1W120B or approved equivalent	
	Document Camera	Desktop style with HDMI output	Epson, QOMO or approved equivalent	
	Blu-ray Player	Blu-ray player with HDMI output.	Sony BDP-S5500 or approved equivalent	
	Wired lavalier microphone	Must provide clear non-interference sound	Audio Technica AT-831R or approved equivalent	
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system		

Complete Podium	Teaching Podium	Native Maple finish, custom base, 33" turret frame with vented rack inserts, trim and finishing kits with custom cut out for specified control panel.	Middle Atlantic L5TURFRW33, L5TKK33NT, FIN-NM, and L5-CUSTPNL-33 Podium with L5-SHOC-XLR-S and L5-Tasklight18 or approved equivalent
	Networking switch	<p>Policy-based access control, identity and role-aware network, data integrity and confidentiality. Layer 2 threat defense capabilities with integrated security features for flexible collaboration between users on the network. Compliance with Payment Card Industry Data Security Standard (PCI DSS) to meet regulatory mandates. Physical security with cable guard and lock.</p> <p>Ease of Deployment:</p> <ul style="list-style-type: none"> •Zero touch deployment and ease of troubleshooting •Automatic configuring of the switch based on the type of device connected to the port •State-of-the-art QoS implementation for IP telephony and video <p>Reduce Energy Costs:</p> <ul style="list-style-type: none"> •Support to monitor, manage and reduce energy consumption of the devices connected to the switch <p>Connectivity:</p> <ul style="list-style-type: none"> •8-12 Fast Ethernet or Gigabit Ethernet connectivity •Power over Ethernet (PoE) and PoE pass-through •Two 1-Gb Ethernet uplinks 	Cisco Catalyst 2960C 8 FE PoE or approved equivalent
	Power Management Unit	Must have ethernet control	RLNK-SW815R-SP
	Gooseneck Mic	With shock mount Mic holder and light. For wireless mic mounted to podium	Clock Audio C34E/SR-RF or approved equivalent
	Wireless Mic System with microphone	Must be G3 frequency	Shure ULXS124/85 or approved equivalent
	Audio Amplifier	Only if Wattage of speakers exceed Extron Crosspoint 84 Amplifier wattage	Extron, QSC, JBL or approved equivalent
	USB Switcher	Features with emulation for Smart software functionality between PC and laptop. Four-input USB switchers that allow switching between multiple host devices and multiple USB peripherals. Integrator-friendly for implementing USB 2.0 compatible switching. Streamline integration such as: port status indication, RS-232 pass-through, front panel security lockout, and multiple control points. Host and Peripheral Emulation Mode, which provides "keep alive" functionality by continuously mimicking host and keyboard/mouse communications within the switcher. Eliminates the need for enumeration, and reduction in the chance of failed device communications throughout the switching process.	Extron SW4 USB 60-954-02 or approved equivalent
	Captive Cable Kit	plate with one large hole and two small	Extron 70-317-13 or approved equivalent
	Grommet Plate	for VGA/Audio Cable	Extron 70-317-12 or approved equivalent
	Adapters	CSM 6 captive screw to female adapter. Display Port to HDMI adaptor for PC to switcher audio	Extron or approved equivalent
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system	
	Wiremold	Over Floor Raceway	color: black

Exhibit 3
Classroom Standards

Standard Hi-Tech with iTV Classroom AV Equipment (Quantities determined by design)

as of July 2016

	Item	Features and Performance requirements	Performance Product
Audio/Video Displays	Commercial grade rear monitor	Monitor with RS-232 control and HDMI inputs to be viewed by system user from teaching station. Size determined by room size.	NEC
	Commercial grade front reinforcement monitor(s)	Monitor with RS-232 control and HDMI. Quantity and size determined by room size.	NEC
	Wall Mount	For Confidence and Reinforcement Monitors. Required for rooms that have a ceiling height of nine (9) feet or more. Must have 180 degree radius and security features.	Chief or approved equivalent
	Ceiling Mount	For Confidence and Reinforcement Monitors. Required for rooms that have a ceiling height of nine (9) feet or more and ceiling material of lay-in accoustical tile. Must have 180 degree radius and security features.	Chief or approved equivalent
	Laser Video Projector w/ Mount	With HDMI input RS-232 control and HDBaseT Input. Lensing and brightness determined by screen size and room light conditions. Ceiling mount to be compatible with the for selected projector. Must have security features.	Sony VPL-FHZ57W projector or approved equivalent Chief RPA-020 Mount or approved equivalent
	Projection Screen and Switch Control	Screen size shall be determined by 9' ceiling height mounting needs. Motorized contrast grey preferred. Switch mounted on wall for screen control.	Draper, Da-Lite, or approved equivalent
	Ceiling Speakers	Must provide appropriate number of speakers for complete room coverage.	Sound Advance, JBL or approved equivalent
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system	
Control Equipment	Central Room Control TouchPanel Power Connections Power Supply	7" Touch Panel for room control Power over ethernet for touch panel if required Low voltage interface to integrate screen control with control system Power Supply for AMX controller	AMX MSD-701-L or MST-701 AMX PS-POE AF TC AMX PS4.4
	Master Controller	The NX-3200 / NetLinx® NX Integrated Controller is a programmable network appliance specifically designed to control AV and building technology using multiple analog and digital formats. The NX-2200 provides a scalable platform for the future by combining high performance, backward compatibility and extensive network security features	AMX NX-3200
Video Switching / Processing Equipment	Scaling matrix switcher switcher.	All-in-one 8x4 matrix switcher, scaler, audio DSP, audio power amplifier, and control processor	Extron DTP CrossPoint 84 IPCP MA 70 - 60-1368-13
	Digital Video Transmitter/Receiver	Long distance transmitter for sending HDMI, audio, and bidirectional RS-232 and IR signals up to 330 feet (100 meters) over a shielded CATx cable to enabled products. Extending HDMI with embedded multi-channel audio from HDMI-equipped devices and accepts analog stereo audio signals for simultaneous transmission over the same shielded twisted pair cable. It supports video signals at resolutions up to 4K. Compact enclosure size and remote power capability.	Extron DTP HDMI 330 TX , 60-1331-12 or approved equivalent
	Digital Receiver	Long distance, digital twisted pair receiver that works with the transmitter to send HDMI, audio, and bidirectional RS-232 and IR signals up to 330 feet (100 meters) over a shielded CATx cable. Extended HDMI with embedded multi-channel audio from HDMI-equipped devices. Accepts analog stereo audio signals over the same shielded twisted pair cable. Supports video signals at resolutions up to 4K. Compact enclosure size and remote power capability for discreet placement in lecterns and behind flat-panel displays.	Extron DTP HDMI 330 RX, 60-1331-13 or approved equivalent
	HDMI video DA	HDMI Distrubution Amplifier for output to Front and Rear Monitors for Video Conferencing	Extron or approved equivalent

Video Source equipment	Annotation Tablet w/ 2 Pens and Desk Monitor Arm	Digital HD 18.5" preview monitor with ability to annotate using Smart Technologies software. And Swiveling monitor arm to attach preview monitor to podium	Smart Tablet SP-518NB or approved equivalent Smart Pen 20-01545-20 or approved equivalent Chief monitor arm K1W120B or approved equivalent
	Document Camera	Desktop style with HDMI output	Epson, QOMO or approved equivalent
	Blu-ray Player	Blu-ray player with HDMI output.	Sony BDP-S5500 or approved equivalent
	Wired lavalier microphone	Must provide clear non-interference sound	Audio Technica AT-831R or approved equivalent
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system	
Complete Podium	Teaching Podium	Native Maple finish, custom base, 33" turret frame with vented rack inserts, trim and finishing kits with custom cut out for specified control panel.	Middle Atlantic L5TURFRW33, L5GTK33NT, FIN-NM, and L5-CUSTPNL-33 Podium with L5-SHOC-XLR-S and L5-Tasklight18 or approved equivalent
	Networking switch	<p>Policy-based access control, identity and role-aware network, data integrity and confidentiality. Layer 2 threat defense capabilities with integrated security features for flexible collaboration between users on the network. Compliance with Payment Card Industry Data Security Standard (PCI DSS) to meet regulatory mandates. Physical security with cable guard and lock.</p> <p>Ease of Deployment:</p> <ul style="list-style-type: none"> •Zero touch deployment and ease of troubleshooting •Automatic configuring of the switch based on the type of device connected to the port •State-of-the-art QoS implementation for IP telephony and video <p>Reduce Energy Costs:</p> <ul style="list-style-type: none"> •Support to monitor, manage and reduce energy consumption of the devices connected to the switch <p>Connectivity:</p> <ul style="list-style-type: none"> •8-12 Fast Ethernet or Gigabit Ethernet connectivity •Power over Ethernet (PoE) and PoE pass-through •Two 1-Gb Ethernet uplinks 	Cisco Catalyst 2960C 8 FE PoE or approved equivalent

Podium Continue	Gooseneck Mic	With shock mont Mic holder and light. For wireless mic mounted to podium	Clock Audio C34E/SR-RF or approved equivalent
	Power Management Unit	Must have ethernet control	RLNK-SW815R-SP
	Wireless Mic System w/microphone	Must be G3 frequency	Shure ULXS124/85 or approved equivalent
	Audio Amplifier	Only if Wattage of speakers exceed Extron Crosspoint 84 Amplifier wattage	Extron, QSC, JBL or approved equivalent
	USB Switcher	Features with emulation for Smart software functionality between PC and laptop. Four-input USB switchers that allow switching between multiple host devices and multiple USB peripherals. Integrator-friendly for implementing USB 2.0 compatible switching. Streamline integration such as: port status indication, RS-232 pass-through, front panel security lockout, and multiple control points. Host and Peripheral Emulation Mode, which provides "keep alive" functionality by continuously mimicking host and keyboard/mouse communications within the switcher. Eliminates the need for enumeration, and reduction in the chance of failed device communications throughout the switching process.	Extron SW4 USB 60-954-02 or approved equivalent
	Captive Cable Kit	plate with one large hole and two small	Extron 70-317-13 or approved equivalent
	Grommet Plate	for VGA/Audio Cable	Extron 70-317-12 or approved equivalent
	Adapters	CSM 6 captive screw to female adapter. Display Port to HDMI adaptor for PC to switcher audio	Extron or approved equivalent
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system	
Videoconference Equipment		The audio and video engine to incorporate high-definition video collaboration applications into large meeting rooms. See weblink for all features and capabilities. http://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-quick-set-series/datasheet-c78-731242.html	
	Video Conference Codec	SX80 Codec	Cisco CTS-SX80-IPST60-K9
	Cameras and Camera Mounting Hardware	Wall Mount Kit for Speaker Track 60 Microphone Array	Cisco CTS-ST-ARR60-WMK-
		Interface plate CAM-P60 to Speaker Track 60	Cisco CTS-ST-INT-PLATE-
		Bracket for mounting of Precision 60 Camera	Cisco CTS-CAM60-BRKT
		Speaker Track 60 Microphone Array	Cisco CTS-ST-ARRAY60+
		Cisco TelePresence Precision 60 Camera - auto expand only	Cisco CTS-CAM-P60+
		TelePresence Precision 60 Camera	Cisco CTS-CAM-P60
	Touch Panel	Touch 10 auto expand	Cisco CTS-CTRL-DVX-10+
	Miscellaneous	Pwr Cord US 1.8m Black YP-12 To YC-12	Cisco PWR-CORD-US-A
		12.5 meter flat grey Ethernet cable for Touch 10	Cisco CAB-DV10-12.5M
		Presentation cable w/audio VGA/Jack to DVI/Phoenix	Cisco CAB-DVI-VGA-PHOEN
		Two Ethernet cables (0.35m & 0.2m) for SpeakerTrack 60	Cisco CAB-ETH-ST-SHORT-
		Two 12V power cables (0.45m & 0.2m) for SpeakerTrack 60	Cisco CAB-PWR-ST-SHORT-
		Power supply 12VDC 84W	Cisco PWR-12VDC-84W-
		SX80 rack ears - for auto expand only	Cisco CTS-SX80-RACKEARS- Hi Tech w/TV - 3 of 4

Video Conference Equipment Continue	Miscellaneous	4 meter flat grey Ethernet cable for Touch 10	Cisco CAB-DV10-4M
		Power Injector (802.3af)	Cisco CTS-PWR-AIR-INJ5+
		Power Supply 12 VDC 40W	Cisco PSU-12VDC-40W2
		Power Cord US 1.8m Black YP-12 To YC-12	Cisco PWR-CORD-US-A
		Installation sheet for Precision 60 Camera bracket	Cisco DOC-P60CAM-BRKT
	Microphone	TelePresence Table Microphone 60	Cisco CTS-MIC-TABL60
	Ceiling Microphone	Universal AudioScience Mounting Kit	Cisco CTS-MTKIT-UA
		Ceiling Microphone Gen 2 stand alone kit	Cisco CTS-MIC-CLNG-G2=
		Ceiling Mic. dongles, RJ45-Euroblock and RJ45-MiniJack Spare	Cisco CTS-MIC-CLNG-DNG=
		Ceiling Microphone parts - Ceiling mounting wire kit Spare	Cisco CTS-MIC-CLNG-WRK=
		Microphone element for Ceiling Microphone Spare	Cisco CTS-MIC-CLNG-ELM=
		Ceiling Microphone parts - Top and Back plates Spare	Cisco CTS-MIC-CLNG-PLT=
	License Key or Serice Warranty	Remote monitoring options for TelePresence Endpoints	Cisco L-TP-RM
		Remote monitoring option for SX series Endpoints	Cisco L-SX-SERIES-RM
		ESS WITH 8X5XNBD Cisco SX80 Codec Speaker Trk 60 Touch	Cisco CON-ECDN-SX80IP60
		License key to activate sw encryption module	Cisco LIC-TC-CRYPTO-K9
		ESS WITH 8X5XNBD Cisco TelePresence Precision 60 Camera	Cisco CON-ECDN-CTSCAM60
		ESS WITH 8X5XNBD Cisco TelePresence Table Microphone 60	Cisco CON-ECDN-CTSMICTB
		SW Image for SX80 MX700 MX800	Cisco SW-S52020-TC7-K9

Exhibit 4
Classroom Standards

Lecture Hall and Auditoria AV Equipment (Quantities determined by design)
capacity for 100 students and up

as of July 2016

	Item	Features and Performance requirements	Performance Product
Audio / Video Displays	Commercial grade rear monitor	Monitor with RS-232 control and HDMI inputs to be viewed by system user from teaching station. Size determined by room size.	NEC
	Commercial grade front reinforcement monitor(s)	Monitor with RS-232 control and HDMI. Quantity and size determined by room size.	NEC
	Wall Mount	For Confidence and Reinforcement Monitors. Required for rooms that have a ceiling height of nine (9) feet or more. Must have 180 degree radius and security features.	Chief or approved equivalent
	Ceiling Mount	For Confidence and Reinforcement Monitors. Required for rooms that have a ceiling height of nine (9) feet or more and ceiling material of lay-in accoustical tile. Must have 180 degree radius and security features.	Chief or approved equivalent
	Laser Video Projector w/ Mount	With HDMI input RS-232 control and HDBaseT Input. Lensing and brightness determined by screen size and room light conditions. Ceiling mount to be compatible with the for selected projector. Must have security features.	Sony VPL-FHZ57W projector or approved equivalent Chief RPA-020 Mount or approved equivalent
	Projection Screen and Switch Control	Screen size shall be determined by 9' ceiling height mounting needs. Motorized contrast grey preferred. Switch mounted on wall for screen control.	Draper, Da-Lite, or approved equivalent
	Ceiling Speakers	Must provide appropriate number of speakers for complete room coverage.	Sound Advance, JBL or approved equivalent
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system	
Control Equipment	Central Room Control TouchPanel Power Connections	7" Touch Panel for room control Power over ethernet for touch panel if required Low voltage interface to integrate screen control with control system	AMX MSD-701-L or MST-701 AMX PS-POE AF TC
	Master Controller	The NX-3200 / NetLinx® NX Integrated Controller is a programmable network appliance specifically designed to control AV and building technology using multiple analog and digital formats. The NX-2200 provides a scalable platform for the future by combining high performance, backward compatibility and extensive network security features	AMX NX-3200
Video Switching / Processing Equipment	Scaling matrix switcher switcher.	All-in-one 8x4 matrix switcher, scaler, audio DSP, audio power amplifier, and control processor	Extron DTP CrossPoint 84 IPCP MA 70 - 60-1368-13
	Digital Video Transmitter/Receiver	Long distance transmitter for sending HDMI, audio, and bidirectional RS-232 and IR signals up to 330 feet (100 meters) over a shielded CATx cable to enabled products. Extending HDMI with embedded multi-channel audio from HDMI-equipped devices and accepts analog stereo audio signals for simultaneous transmission over the same shielded twisted pair cable. It supports video signals at resolutions up to 4K. Compact enclosure size and remote power capability.	Extron DTP HDMI 330 TX , 60-1331-12 or approved equivalent
	Digital Receiver	Long distance, digital twisted pair receiver that works with the transmitter to send HDMI, audio, and bidirectional RS-232 and IR signals up to 330 feet (100 meters) over a shielded CATx cable. Extended HDMI with embedded multi-channel audio from HDMI-equipped devices. Accepts analog stereo audio signals over the same shielded twisted pair cable. Supports video signals at resolutions up to 4K. Compact enclosure size and remote power capability for discreet placement in lecterns and behind flat-panel displays.	Extron DTP HDMI 330 RX, 60-1331-13 or approved equivalent
	HDMI video DA	HDMI Distribution Amplifier for output to Front and Rear Monitors for Video Conferencing	Extron or approved equivalent
	Video PIP Device	Seamless scaller for Picture in Picture	DVS 605
Video Source Equipment	Annotation Tablet w/ 2 Pens and Desk Monitor Arm	Digital HD 18.5" preview monitor with ability to annotate using Smart Technologies software. And Swiveling monitor arm to attach preview monitor to podium	Smart Tablet SP-518NB or approved equivalent Smart Pen 20-01545-20 or approved equivalent Chief monitor arm K1W120B or approved equivalent

Video Source Equipment Continue	Document Camera	Desktop style with HDMI output	Epson, QOMO or approved equivalent
	Blu-ray Player	Blu-ray player with HDMI output.	Sony BDP-S5500 or approved equivalent
	Wired lavalier microphone	Must provide clear non-interference sound	Audio Technica AT-831R or approved equivalent
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system	
Complete Podium	Teaching Podium	Native Maple finish, custom base, 33" turret frame with vented rack inserts, trim and finishing kits with custom cut out for specified control panel.	Middle Atlantic L5TURFRW43, L5KTK43NT, FIN-NM, and L5-CUSTPNL-43 Podium with L5-SHOC-XLR-S and L5-Tasklight18 or approved equivalent
	Networking switch	Policy-based access control, identity and role-aware network, data integrity and confidentiality. Layer 2 threat defense capabilities with integrated security features for flexible collaboration between users on the network. Compliance with Payment Card Industry Data Security Standard (PCI DSS) to meet regulatory mandates. Physical security with cable guard and lock. Ease of Deployment: •Zero touch deployment and ease of troubleshooting •Automatic configuring of the switch based on the type of device connected to the port •State-of-the-art QoS implementation for IP telephony and video Reduce Energy Costs: •Support to monitor, manage and reduce energy consumption of the devices connected to the switch Connectivity: •8-12 Fast Ethernet or Gigabit Ethernet connectivity •Power over Ethernet (PoE) and PoE pass-through •Two 1-Gb Ethernet uplinks	Cisco Catalyst 2960C 8 FE PoE or approved equivalent
	Gooseneck Mic	With shock mont Mic holder and light. For wireless mic mounted to podium	Clock Audio C34E/SR-RF or approved equivalent
	Wireless Mic System w/microphone	Must be G3 frequency	Shure ULXS124/85 or approved equivalent
	Audio Amplifier	Only if Wattage of speakers exceed Extron Crosspoint 84 Amplifier wattage	Extron, QSC, JBL or approved equivalent
	USB Switcher	Features with emulation for Smart software functionality between PC and laptop. Four-input USB switchers that allow switching between multiple host devices and multiple USB peripherals. Integrator-friendly for implementing USB 2.0 compatible switching. Streamline integration such as: port status indication, RS-232 pass-through, front panel security lockout, and multiple control points. Host and Peripheral Emulation Mode, which provides "keep alive" functionality by continuously mimicking host and keyboard/mouse communications within the switcher. Eliminates the need for enumeration, and reduction in the chance of failed device communications throughout the switching process.	Extron SW4 USB 60-954-02 or approved equivalent
	Hearing Assist Listening Device		LS-51-072, LA-125
	Captive Cable Kit	plate with one large hole and two small	Extron 70-317-13 or approved equivalent
	Grommet Plate	for VGA/Audio Cable	Extron 70-317-12 or approved equivalent
	Adapters	CSM 6 captive screw to female adapter. Display Port to HDMI adaptor for PC to switcher audio	Extron or approved equivalent
	Miscellaneous	All cables connectors and hardware necessary to install a complete working system	
Video Conference / Streaming Equipment	Video Conference Codec	Cisco SX20 with 12X camera	CTS-SX20-PHD12X-K9
	Maintenance	8x5xNBD service	CON-ECDN-SX2PHD12
	Remote monitoring option	option key	L-SX-SERIES-RM
	Camera cable adapter	break out cable	CAB-PHD4XS2-SPLIT=

Exhibit 5
Classroom Standards

Basic VTC Conference Room Equipment (Quantities determined by design)
capacity 16 people

as of July 2016

	Item	Features and Performance requirements	Performance Product
Audio / Video Displays	Monitor	RS-232 control appropriate size for room	NEC comercial or approved equal
	Mount	Mount for Monitor (wall or ceiling, room dictates type)	Chief or approved equal
Video Switching / Processing Equipment	Video Scaler	Video scaler to scale duo video channel for video conference system	Extron HD-HD or equivalent
	HDMI DA	HDMI DA to split content to video conference system and monitor	Extron or approved equal
Video Source Equipment	Input Wall Plate	Wall plate to plug laptop/other sources into. Must have HDMI and VGA	Extron or approved equal
Video Conference Equipment	Camera and Condec	Video conference codec with maintenance warranty	CTS-SX10-K9, CON-PSRN-CTSSX10
Control Equipment	Wall Push Button Control Device	Push button system on the wall to control the inputs and monitor	SP Systems Pixie Plus or approved equal

Exhibit 6 Executive VTC Conference Room Equipment (Quantities determined by design) capacity 20 people				as of July 2016
	Item	Features and Performance requirements	Performance Product	
Audio/Video Displays	Monitor	RS-232 control	NEC comercial or equivalent	
	Mount	Mount for Monitor	Chief or equivalent	
Video Switching / Processing Equipment	Video Scaler	Video scaler to scale duo video channel for video conference system	HD-HD	
	Scaling AV Switcher	IN-1606 AV switcher. 4 HDMI inputs, 2 VGA inputs, 2 HDMI scaleable outputs with audio level control.	Extron IN1606 HDCP-Compliant Scaling Switcher 60-1081-01	
Video Source Equipment	Input Wall Plate	Wall plate to plug laptop/other sources into. Must have HDMI and VGA		
Video Conference Equipment	Cisco SX10	Video conference codec with maintenance warranty	CTS-SX10-K9, CON-PSRN-CTSSX10	
Control Equipment	Master Controller	The NX-2200 / NetLinx® NX Integrated Controller is a programmable network appliance specifically designed to control AV and building technology using multiple analog and digital formats. The NX-2200 provides a scalable platform for the future by combining high performance, backward compatibility and extensive network security features. The NX-2200 is ideal for control and automation of medium-sized rooms and multi-room applications, as it includes more ports and security capabilities than the NX-1200.	AMX NX-2200	
	Central Room Control TouchPanel Power Connections Power Supply	7" Touch Panel for room control Power over ethernet for touch panel if required Low voltage interface to integrate screen control with control system Power Supply for AMX controller	AMX MSD-701-L or MST-701 AMX PS-POE AF TC AMX PS4.4	
Rack/Podium	Networking switch	Policy based access control, identity and role aware network, data integrity and confidentiality. Layer 2 threat defense capabilities with integrated security features for flexible collaboration between users on the network. Compliance with Payment Card Industry Data Security Standard (PCI DSS) to meet regulatory mandates. Physical security with cable guard and lock. Ease of Deployment: •Zero touch deployment and ease of troubleshooting •Automatic configuring of the switch based on the type of device connected to the port •State-of-the-art QoS implementation for IP telephony and video Reduce Energy Costs: •Support to monitor, manage and reduce energy consumption of the devices connected to the switch Connectivity: •8-12 Fast Ethernet or Gigabit Ethernet connectivity •Power over Ethernet (PoE) and PoE pass-through •Two 1-Gb Ethernet uplinks	Cisco Catalyst 2960C 8 FE PoE or approved equivalent	
	16U Rack	VFI REX16 equipment Rack		